



Tarasafe Standard - Sheet

Generated on 08.03.2019

Detailed description

Tarasafe Standard is a recyclable, R10 rated slip resistant sheet floor covering with PUR surface treatment that meets HSE guidelines. It is constructed from vinyl with inlaid mineral crystal particles and reinforced with a glass fibre grid. The joints are hot-welded to ensure perfect water tightness.

Suitable for use in all areas of heavy traffic where slip-resistance, durability and hygienic conditions are required.

12 year warranty and is 100% recyclable, when the product is at the end of its life.

Product guidance - As Standard

Width:

2.0 m.

Length:

20.0 m.

Thickness:

2.0 mm.

Weight:

2210 g/m².

BS EN 651 wear group:

T.

BS EN 685 level of use class:

34-43 – Commercial, very heavy – Light industrial, heavy.

BS 7976 Pendulum Test Value (PTV):

≥ 36.

Slip resistance class to DIN 51130 (ramp test) – wet with oil:

R10 – The scale runs from R9 to R13, where R9 is the most slippery and R13 the least slippery.

BS EN 1815 static electricity electrical propensity:

<2 kV.

BS EN 12524 thermal conductivity:

Gerflor Ltd



Gerflor Ltd
Wedgnoek House
Wedgnoek Lane
Warwick
Warwickshire
CV34 5AP

Tel: +44 (0)1926 622600

www.gerflor.co.uk
contractuk@gerflor.com



0.25 W/(m.K).

Welding rods:

Supplied in a range of standard colours, manufacturer matched to each individual floor covering.

Product specification

Manufacturer

- Name: Gerflor Ltd
- Web: www.gerflor.co.uk
- Email: contractuk@gerflor.com
- Tel: +44 (0)1926 622600
- Fax: +44 (0)1926 401647
- Address: Wedgnock House, Wedgnock Lane, Warwick, Warwickshire CV34 5AP

Product reference Tarasafe Standard - Sheet

Colour [_____]