

# Elevator Equipment Limited

11-13 Parker Drive, Leicester. LE4 0JP  
Tel: **0116 2662241**  
Fax: **0116 2662242**  
E-Mail: [sales@elevator-equipment.co.uk](mailto:sales@elevator-equipment.co.uk)  
Website: [www.elevator-equipment.co.uk](http://www.elevator-equipment.co.uk)

---

## LAMP CHARACTERISTICS

### Benefits

- Energy saving up to 95%
- No IR and UV radiation.
- Mercury free.

### Electrical Characteristics

- Nominal power consumption 2,7W
- Rated power consumption 2,7W
- Nominal Operating Voltage 210-240V
- Lamp equivalent 50W
- Rated efficacy 145 lm/W
- Operating frequency 50 - 60Hz
- Operating current 0,086A
- Power Factor 0,99
- CRI 75

### Lighting characteristics

- Beam angle 120 °
- Number of LEDs 48
- Nominal luminous flux (6000K) 391lm
- Rated luminous flux (6000K) 391lm
- Colour Temperature 6000k (Cool White)
- Rated Lifetime: 50.000 hrs

### EASY TO INSTALL:

Prior to despatch, all our kits are fully tested and pre-wired. All you need to do is fit the lamps into the ceiling. Find a suitable place to mount the mains/emergency unit, connect up the battery and find a 230V power supply.

#### Lamp depth 35mm -

Aluminium Nickel Plated extensions rings are available to allow these lamps to fitted into holes up to 84mm. We stock cool white light lamps. Warm White available by special request.

### IMPORTANT NOTE

These lighting kits must be wired directly into a constant 230V supply. Some control systems have power saving devices, you must not connect to systems of this nature.

