



SKU : SL4515-CW
SL4515-NW
SL4515-WW



45w 5ft low profile surface batten fitting with a extra high lumen output, perfect for office, showroom or warehouse lighting providing a 110° beam angle to maintain a even distribution of light output. Low energy consumption as opposed to the halogen/flourescent fittings & slim low profile look for a much sleeker finish. Suitable for surface mounting, easy to install with clip on brackets. This product is suitable for domestic and commercial applications as replacement for traditional flourescent light fittings. 2m cable built in to the fitting for easy installation.

DETAILS

Product Type:	LED Batten
Product Body Finish:	White Body
Market Segment:	Commercial & Domestic application
Warranty (Years):	3
CE RoHS:	Yes
UKCA:	Yes

PHYSICAL DATA

Product Length (mm):	1500
Product Depth (mm):	24
Product Width (mm):	75
Product Weight (g):	1150g
Optic:	Opal Diffuser
Material:	Aluminium Housing/Polycarbonate Diffuser
Placement / Application:	Indoor Lighting

ELECTRICAL DATA

Power (W):	45W
Power Consumption (w):	45W
Power Factor:	>0.95
Amperage (mA):	
Dimming:	Non-Dimmable
Driver Included:	Built-in Driver
Electric Current:	AC



**SKU : SL4515-CW
SL4515-NW
SL4515-WW**

LIGHT DATA

Luminous Flux in Lumens (lm):	4500
Luminous efficacy (lm/W):	100
Correlated Colour Temperature (CCT) (K):	3000k, 4000k or 6000k
Beam Angle:	110°
Colour Rendering Index (CRI):	>80 RA
Frequency Range (Hz):	50/60
LED Type:	SMD 2835 EPISTAR LED
Lifetime (hours):	50,000 Hrs
Emergency Compatible:	Yes - With emergency battery pack (EL05UPK)

ENVIRONMENT

UKCA:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Back/Recessed side):	IP20
IP Rating (Ingress Protection):	IP20
Fire Rated:	No
Lowest Operating Temperature (°C):	-20°
Maximum Operating Temperature (°C):	40°