



No. TX F310-014-15 0153

Applicant's name and

address:

Dynatech, Dynamics & Technolgy, S.L.U

Poligono Industrial Pina de Ebro, Sector C P9,

Zaragoza, Spain

Manufacturer's name

and address:

Dynatech, Dynamics & Technolgy, S.L.U

Poligono Industrial Pina de Ebro, Sector C P9,

Zaragoza, Spain

Name of product

Two-way overspeed governor

(Type of equipment):

(Overspeed governor)

Model and specifications: VEGA

Rated speed: 1.00m/s

Configuration of product: Configuration of overspeed governor (See appendix)

Type test report No.:

T14-F31-15-153

This certificate is valid for products of the models and specifications below (without change of the product configuration): /

After type test, this product is accord with Regulation for type tests of lifts (2012), Rule for type test of overspeed governors (2012), GB7588 - 2003 and EN81-1:1998.

Issue dates

NETEC

National Elevator Inspection and Testing

Note:

1. This certificate is to confirm the products on type and the tested sample on conformity, only valid for the products that are in conformance with the tested sample mentioned above.

Configuration of Overspeed Governor

Structure type	Centrifugal type
Type of safety gear which will be operated	Progressive safety gear
Rated speed	1.00m/s
The diameter of the rope to be used and its construction	6×19S+FC <i>ϕ</i> 6mm
Tensioning weights suspension mode	Lever vertical suspension
Minimum tensioning weight	25kg
Special working environment	1

Issue date

4 4







No. TX F310-014-15 0154

Applicant's name and

Dynatech, Dynamics & Technolgy, S.L.U

address:

Poligono Industrial Pina de Ebro, Sector C P9,

Zaragoza, Spain

Manufacturer's name

Dynatech, Dynamics & Technolgy, S.L.U

and address:

Poligono Industrial Pina de Ebro, Sector C P9,

Zaragoza, Spain

Name of product

Two-way overspeed governor

(Type of equipment):

(Overspeed governor)

Model and specifications: VEGA

Rated speed: 1.50m/s

Configuration of product: Configuration of overspeed governor (See appendix)

Issue date:

Type test report No.:

T14-F31-15-154

This certificate is valid for products of the models and specifications below (without change of the product configuration): /

After type test, this product is accord with Regulation for type tests of lifts (2012), Rule for type test of overspeed governors (2012), GB7588 — 2003 and EN81-1:1998.

NETEC

National Elevator Inspection and Testing Center

Note:

1. This certificate is to confirm the products on type and the tested sample on conformity, only valid for the products that are in conformance with the tested sample mentioned above.

Configuration of Overspeed Governor

Structure type	Centrifugal type
Type of safety gear which will be operated	Progressive safety gear
Rated speed	1.50m/s
The diameter of the rope to be used and its construction	6×19S+FC <i>ϕ</i> 6mm
Tensioning weights suspension mode	Lever vertical suspension
Minimum tensioning weight	25kg
Special working environment	1









No. TX F310-014-15 0155

Applicant's name and

address:

Dynatech, Dynamics & Technolgy, S.L.U

Poligono Industrial Pina de Ebro, Sector C P9,

Zaragoza, Spain

Manufacturer's name

and address:

Dynatech, Dynamics & Technolgy, S.L.U

Poligono Industrial Pina de Ebro, Sector C P9,

Zaragoza, Spain

Name of product

Two-way overspeed governor

(Type of equipment):

(Overspeed governor)

Model and specifications: VEGA

Rated speed: 1.60m/s

Configuration of product: Configuration of overspeed governor (See appendix)

Issue date: 201

Type test report No.:

T14-F31-15-155

This certificate is valid for products of the models and specifications below (without change of the product configuration): /

After type test, this product is accord with Regulation for type tests of lifts (2012), 2003 and Rule for type test of overspeed governors (2012), EN81-1:1998.

NETEC

National Elevator Inspection and Testing C

Note:

1. This certificate is to confirm the products on type and the tested sample on conformity, only valid for the products that are in conformance with the tested sample mentioned above.


Configuration of Overspeed Governor

Structure type	Centrifugal type
Type of safety gear which will be operated	Progressive safety gear
Rated speed	1.60m/s
The diameter of the rope to be used and its construction	6×19S+FC <i>ϕ</i> 6mm
Tensioning weights suspension mode	Lever vertical suspension
Minimum tensioning weight	25kg
Special working environment	1

Issue date: 2015-12-0年 於股报告专用章







No. TX F310-014-15 0156

Applicant's name and

address:

Dynatech, Dynamics & Technolgy, S.L.U

Poligono Industrial Pina de Ebro, Sector C P9,

Zaragoza, Spain

Manufacturer's name

and address:

Dynatech, Dynamics & Technolgy, S.L.U

Poligono Industrial Pina de Ebro, Sector C P9,

Zaragoza, Spain

Name of product

Two-way overspeed governor

(Type of equipment):

(Overspeed governor)

Model and specifications: VEGA

Rated speed: 1.75m/s

Configuration of product: Configuration of overspeed governor (See appendix)

Issue date

Type test report No.:

T14-F31-15-156

This certificate is valid for products of the models and specifications below (without change of the product configuration): /

After type test, this product is accord with Regulation for type tests of lifts (2012), Rule for type test of overspeed governors (2012), GB7588 2003 and EN81-1:1998.

NETEC

National Elevator Inspection and Testing Center

Note:

1. This certificate is to confirm the products on type and the tested sample on conformity, only valid for the products that are in conformance with the tested sample mentioned above.

Configuration of Overspeed Governor

Structure type	Centrifugal type
Type of safety gear which will be operated	Progressive safety gear
Rated speed	1.75m/s
The diameter of the rope to be used and its construction	6×19S+FC <i>ϕ</i> 6mm
Tensioning weights suspension mode	Lever vertical suspension
Minimum tensioning weight	25kg
Special working environment	1

Issue date: ZouS-12至4 位型 检验报告专用章







No. TX F310-014-15 0157

Applicant's name and

Dynatech, Dynamics & Technolgy, S.L.U

address:

Poligono Industrial Pina de Ebro, Sector C P9,

Zaragoza, Spain

Manufacturer's name

Dynatech, Dynamics & Technolgy, S.L.U

and address:

Poligono Industrial Pina de Ebro, Sector C P9,

Zaragoza, Spain

Name of product

Two-way overspeed governor

(Type of equipment):

(Overspeed governor)

Model and specifications: VEGA

Rated speed: 2.00m/s

Configuration of product: Configuration of overspeed governor (See appendix)

Issue date:

Type test report No.:

T14-F31-15-157

This certificate is valid for products of the models and specifications below (without change of the product configuration): /

After type test, this product is accord with Regulation for type tests of lifts (2012), Rule for type test of overspeed governors (2012), 2003 and EN81-1:1998.

NETEC

National Elevator Inspection and Testing Center

1. This certificate is to confirm the products on type and the tested sample on conformity, only valid for the products that are in conformance with the tested sample mentioned above.

Configuration of Overspeed Governor

Structure type	Centrifugal type
Type of safety gear which will be operated	Progressive safety gear
Rated speed	2.00m/s
The diameter of the rope to be used and its construction	6×19S+FC φ6mm
Tensioning weights suspension mode	Lever vertical suspension
Minimum tensioning weight	25kg
Special working environment	1

Issue date: 20以 12-04 检验报告专用章