












Tornado EVO


Tornado EVO CCT Multi Wattage 1500mm Code: ATORE5/1











PRODUCT FEATURES

- IP65 non-corrosive batten suitable for industrial applications and ancillary areas
- CCT selectable between 4000K, 5000K and 6500K and power selectable; offering a choice of 2 outputs, in one luminaire
- $\bullet~$ LED performance allows point-to-point replacement of existing fluorescent luminaires
- Whole luminaire illuminates during emergency operation rather than a small area, allowing less emergency versions required on an installation
- High efficiency up to 160 Lm/W
- Slim sloped diffuser design creates sleek appearance and offers greater light distribution
- Lockable heavy-duty stainless steel clips supplied as standard for added safety and security

| GENERAL INFORMATION | | |
|-------------------------|-------------------------|--|
| Wattage | 30W/60W | |
| Lumens Delivered | 4700lm - 9300lm (4000K) | |
| Lm/W | 160lm/W (4000K) | |
| Beam Angle | 120 | |
| CRI | 80 | |
| CCT | 4000/5000/6500K | |
| Input | 220/240V | |
| Operating Temp | -20°C - 40°C | |
| SDCM | 6 | |
| Energy efficiency class | D | |

www.ansell-lighting.com

| TECHNICAL INFORMATION | | |
|--------------------------------|---------------------|--|
| Light Source | LED | |
| Colour / Finish | Grey | |
| IP Rating | IP65 | |
| Class Protection | 1 | |
| Internal / External | Internal / External | |
| Surface / Recessed / Suspended | Ceiling, Suspended | |
| Lumen Depreciation | L70 54,000h | |
| Warranty (Years) | 5 | |
| CE Mark | Yes | |
| Height | 80 mm | |

Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750