



LED Filament Candle/Round Pearl Dimmable & Non-Dimmable



Energy saving LED replacement lamp featuring LED filament technology to closely resemble the look and feel of a traditional pearl incandescent lamp.

- 15,000 hour life
- 7,500 switching cycles
- 2700K warm white
- Colour rendering index Ra≥80
- BC-B22d, ES-E27 cap SBC-B15d and SES-E14 cap
- Pearl finish
- Dimmable or non-dimmable options
- Dimmable option utilizes DuoDim™ Technology compatible with both leading and trailing edge dimmers*
- For indoor use only

| Product Code | Watts (W) | Volts (V) | Сар | Colour Appearance | Colour Temp | Total Lumens | Incandescent Equivalent (W) | Dimensions (mm) | | Energy Rating | Order Qty |
|-------------------------------------|--------------|--------------|----------|----------------------|----------------|-----------------|-----------------------------------|--------------------|----|------------------|--------------|
| | | | | | (K) | (lm) | | Dia | Н | | |
| Non-Dimmable Candle - Single Carlon | | | | | | | | | | | |
| 5976 | 4 | 240 | BC-B22d | Warm White | 2700 | 470 | 40 | 35 | 91 | A** | 1 |
| 6164 | 4 | 240 | ES-E27 | Warm White | 2700 | 470 | 40 | 35 | 93 | A** | 1 |
| 5983 | 4 | 240 | SES-E14 | Warm White | 2700 | 470 | 40 | 35 | 97 | A** | 1 |
| Dimmable Candle - Single Carton | | | | | | | | | | | |
| 7178 | 5 | 240 | BC-B22d | Warm White | 2700 | 470 | 40 | 35 | 91 | A ⁺ | 1 |
| 7185 | 5 | 240 | SBC-B15d | Warm White | 2700 | 470 | 40 | 35 | 95 | A* | 1 |
| 7192 | 5 | 240 | ES-E27 | Warm White | 2700 | 470 | 40 | 35 | 93 | A* | 1 |
| 7208 | 5 | 240 | SES-E14 | Warm White | 2700 | 470 | 40 | 35 | 97 | A* | 1 |
| Non-Dimmable | Round - | Single | e Carton | | | | | | | | |
| 5990 | 4 | 240 | BC-B22d | Warm White | 2700 | 470 | 40 | 45 | 76 | A** | 1 |
| 6003 | 4 | 240 | ES-E27 | Warm White | 2700 | 470 | 40 | 45 | 78 | A** | 1 |
| 6010 | 4 | 240 | SES-E14 | Warm White | 2700 | 470 | 40 | 45 | 80 | A** | 1 |
| Dimmable Round - Single Carlon | | | | | | | | | | | |
| 7253 | 5 | 240 | BC-B22d | Warm White | 2700 | 470 | 40 | 45 | 76 | A* | 1 |
| 7260 | 5 | 240 | SBC-B15d | Warm White | 2700 | 470 | 40 | 45 | 78 | A* | 1 |
| 7277 | 5 | 240 | ES-E27 | Warm White | 2700 | 470 | 40 | 45 | 78 | A* | 1 |
| 7284 | 5 | 240 | SES-E14 | Warm White | 2700 | 470 | 40 | 45 | 80 | A* | 1 |

* The lamp is compatible with most dimmer switches, please refer to website for up-to-date list of compatible dimmer switches.



Experts in lighting since 1878

Crompton Lamps Limited registered in England and Wales No. 05590551 Registered office and correspondence address: Unit 2, Marrtree Business Park, Bowling Back Lane, Bradford BD4 8QE Tel: +44 (0)1274 657 088 Fax: +44 (0)1274 657 087 Email: sales@cromptonlamps.com Web: www.cromptonlamps.com All images and specifications are for illustration purposes only and are subject to change without notice. E. & O. E. @ Crompton Lamps Limited 2017





Dimmer Compatibility



LED Filament Candle Pearl Dimmable



The below table is designed to help you The below table is designed to help you choose a suitable dimmer switch for your Crompton Lamp dimmable product. Crompton Lamps have extensively tested the below dimmer switches to evaluate their dimming function and to make sure the dimmer switch meets our dimming compatibility drandards compatibility standards.

All compatible dimmer switches may require low end trimming.

For guidelines on dimmer switches not listed below, or for more information please contact Crompton Lamps.

| Manufacturer | Dimmer Model | Dimmer Wattage | Dimmer Type | Lamps Tested Per Circuit | Notes |
|--------------|---------------|-------------------|----------------|-----------------------------|-------------------------------------|
| Aurora | AU-DSP401 | 60W-400W | Leading | 1-5 | Steps 0 - 20% |
| Aurora | AU-DSP651 | 75W-650W | Leading | 1-5 | Steps 0 - 20% Flickers 95 - 100% |
| Aurora | AU-DSP400X | 60W-400W | LED | 1-5 | Slight flicker at all levels |
| Danlers | DQDGEU400W | 40W-400W | Trailing | 1-5 | Does not dim below 50% |
| Danlers | DSS1D 250W | 40W-250W | Leading | 1-5 | Steps 0 - 50% |
| Danlers | DP1D 400WIET | 60W-400W | Leading | 1-5 | Steps 0 - 20% |
| Danlers | DPDLED | 5W-250W | Leading | 1-5 | Steps 0 - 20% |
| MK | K4511xxxLV | 40W-220W | Leading | 1-5 | Dims smooth 0 - 80% |
| МК | K1521WHILV | 40W-300W | Leading | 1-5 | Flickers 75 - 100% |
| MK | K1524WHILV | 40W-300W | Leading | 1-5 | Dims smooth 0 - 80% |
| Zano | ZGRIDLED | 5W-250W | LED | 1-5 | Dims smooth 5 - 100% |
| Zano | ZANOMO500 | 11W-50W | Leading | 1-5 | Dims 0 - 100% Steps 0 - 20% |
| Varilight | V-Pro JQP401W | 10W-400W | Trailing | 1-5 | Dims smooth 0 - 100% |
| Varilight | V-Pro JQP252W | 10W-250W | Trailing | 1-5 | Dims smooth 0 - 100% |
| Eaton | P9131 | 60W-250W | Leading | 1-5 | Dims 0 - 80% Steps 0 - 20% |

The below list of dimmer switches have also been tested by Crompton Lamps and do not meet our dimming compatibility standards. Crompton Lamps does not recommend the use of any of the below dimmer switches as they may cause lamp/dimmer failure.

Danlers: DSS1D 400W



Crompton Lamps Limited registered in England and Wales No. 05590551 Registered office and correspondence address: Unit 2, Marrtree Business Park, Bowling Back Lane, Bradford BD4 8QE

Tel: +44 (0)1274 657 088 Fax: +44 (0)1274 657 087 Email: sales@cromptonlamps.com Web: www.cromptonlamps.com

All images and specifications are for illustration purposes only and are subject to change without notice. E. & O. E. © Crompton Lamps Limited 2017



Dimmer Compatibility



LED Filament Round Dimmable



The below table is designed to help you The below table is designed to help you choose a suitable dimmer switch for your Crompton Lamp dimmable product. Crompton Lamps have extensively tested the below dimmer switches to evaluate their dimming function and to make sure the dimmer switch meets our dimming compatibility drandards compatibility standards.

All compatible dimmer switches may require low end trimming.

For guidelines on dimmer switches not listed below, or for more information please contact Crompton Lamps.

| Manufacturer | Dimmer Model | Dimmer Wattage | Dimmer Type | Lamps Tested Per Circuit | Notes |
|--------------|---------------|-------------------|----------------|-----------------------------|-------------------------------------|
| Aurora | AU-DSP401 | 60W-400W | Leading | 1-5 | Steps 0 - 20% |
| Aurora | AU-DSP651 | 75W-650W | Leading | 1-5 | Steps 0 - 20% Flickers 95 - 100% |
| Aurora | AU-DSP400X | 60W-400W | LED | 1-5 | Slight flicker at all levels |
| Danlers | DQDGEU400W | 40W-400W | Trailing | 1-5 | Does not dim below 50% |
| Danlers | D\$\$1D 250W | 40W-250W | Leading | 1-5 | Steps 0 - 50% |
| Danlers | DP1D 400WIET | 60W-400W | Leading | 1-5 | Steps 0 - 20% |
| Danlers | DPDLED | 5W-250W | Leading | 1-5 | Steps 0 - 20% |
| MK | K4511xxxLV | 40W-220W | Leading | 1-5 | Dims smooth 0 - 80% |
| MK | K1521WHILV | 40W-300W | Leading | 1-5 | Flickers 75 - 100% |
| MK | K1524WHILV | 40W-300W | Leading | 1-5 | Dims smooth 0 - 80% |
| Zano | ZGRIDLED | 5W-250W | LED | 1-5 | Dims smooth 5 - 100% |
| Zano | ZANOMO500 | 11W-50W | Leading | 1-5 | Dims 0 - 100% Steps 0 - 20% |
| Varilight | V-Pro JQP401W | 10W-400W | Trailing | 1-5 | Dims smooth 0 - 100% |
| Varilight | V-Pro JQP252W | 10W-250W | Trailing | 1-5 | Dims smooth 0 - 100% |
| Eaton | P9131 | 60W-250W | Leading | 1-5 | Dims 0 - 80% Steps 0 - 20% |

The below list of dimmer switches have also been tested by Crompton Lamps and do not meet our dimming compatibility standards. Crompton Lamps does not recommend the use of any of the below dimmer switches as they may cause lamp/dimmer failure.

Danlers: DSS1D 400W



Crompton Lamps Limited registered in England and Wales No. 05590551 Registered office and correspondence address: Unit 2, Marrtree Business Park, Bowling Back Lane, Bradford BD4 8QE Tel: +44 (0)1274 657 088 Fax: +44 (0)1274 657 087 Email: sales@cromptonlamps.com Web: www.cromptonlamps.com

All images and specifications are for illustration purposes only and are subject to change without notice. E. & O. E. © Crompton Lamps Limited 2017