

STRONGHOLD LED

A high quality luminaire with clean lines, vandal resistant and tested to BSEN60529:1992 and A2: 2013. On correct installation the Stronghold luminaire can attain Anti Ligature status, tested to the requirement of the National Offenders Management Services.



FEATURES

- Flat opal polycarbonate material as standard
- Manufactured from mild steel
- Rated to IP65 & IK10
- Available with night light function
- Range of outputs available

IK10

IP65


T5
EQUIVALENT

5 YEAR
WARRANTY

TECHNICAL DETAILS

Part Number	Description	Replaces	Weight (kg)	No. Per 10A Breaker	Inrush Current (A)	Circuit Watts (W)	Board Lumens	Luminaire Lumens	Ll/cW
STR 22/2/CO/4K	22W 718mm Single Luminaire	1 x 18W T8	6.5	65	8A 80µs	22	3815	2480	112.7
STR 31/3/CO/4K	31W 1020mm Single Luminaire	1 x 30W T8	9.3	50	5A 37µs	31	5376	3495	112.7
STR 32/4/CO/4K	32W 1325mm Single Luminaire	1 x 36W T8	12.2	35	5A 37µs	32	5550	3607	112.7
STR 44/4/CO/4K	44W 1325mm Single Luminaire	1 x 36W T8	12.2	35	5A 37µs	44	7631	4960	112.7
STR 38/5/CO/4K	38W 1623mm Single Luminaire	1 x 58W T8	13.8	35	5A 37µs	38	6590	4284	112.7
STR 44/5/CO/4K	44W 1623mm Single Luminaire	1 x 58W T8	13.8	25	15A 50µs	44	7631	4960	112.7
STR 48/6/CO/4K	48W 1910mm Single Luminaire	1 x 72W T8	16.2	25	15A 50µs	48	8325	5411	112.7
STR 68/6/CO/4K	68W 1910mm Single Luminaire	1 x 72W T8	16.2	25	15A 50µs	68	11793	7666	112.7

KEY FEATURES



Part Number	Length	Width
STR 11/2/CO/4K	718	265
STR 22/3/CO/4K	1020	265
STR 22/4/CO/4K	1325	265
STR 33/5/CO/4K	1623	265
STR 33/6/CO/4K	1910	265
STR 22/2T/CO/4K	718	265
STR 44/3T/CO/4K	1020	265
STR 44/4T/CO/4K	1325	265
STR 66/5T/CO/4K	1623	265
STR 66/6T/CO/4K	1920	265

OPTIONS AND ACCESSORIES

- EM** Integral Emergency (1W)
- EMST** Integral Emergency Self Test (1W)
- DD** SwitchDIM/DALI
- WL** Wireless Control System
- WLEM** Wireless Monitored Emergency
- SI** Silver
- BK** Black
- 3K** 3000K Colour Temperature
- 5K** 5000K Colour Temperature

PHOTOMETRIC AND DIMENSION

