


Tornado EVO

Tornado EVO CCT Multi Wattage 600mm Code: ATORE2/1









- IP65 non-corrosive batten suitable for industrial applications and ancillary areas
- CCT selectable between 4000K, 5000K and 6500K and power selectable; offering a choice of 2 outputs, in one luminaire
- LED performance allows point-to-point replacement of existing fluorescent luminaires
- Whole luminaire illuminates during emergency operation rather than a small area, allowing less emergency versions required on an installation

GENERAL INFORMATION				
Wattage	9W/18W			
Lumens Delivered	1600lm - 3100lm (4000K)			
Lm/W	160lm/W (4000K)			
Beam Angle	120			
CRI	80			
CCT	4000/5000/6500K			
Input	220/240V			
Operating Temp	-20°C - 40°C			
SDCM	6			
Energy efficiency class	D			

TECHNICAL INFORMATION				
Light Source	LED			
Colour / Finish	Grey			
IP Rating	IP65			
Class Protection	1			
Internal / External	Internal / External			
Surface / Recessed / Suspended	Ceiling, Suspended			
Lumen Depreciation	L70 54,000h			
Warranty (Years)	5			
CE Mark	Yes			
Height	80 mm			

PRODUCT FEATURES

- High efficiency up to 160 Lm/W
- Slim sloped diffuser design creates sleek appearance and offers greater light distribution
- Lockable heavy-duty stainless steel clips supplied as standard for added safety and security

	www.ansell-lighting.com	Warrington:	+44 (0) 1942 43333	3 Belfast: +44 (0)) 2890 773750
--	-------------------------	-------------	--------------------	-------------------	----------------